

BLUENERGY AZURE RHODIUM API CJ-4/SN SERIES

Fully Synthetic-High Performance Multigrade Diesel Engine Oil

PRODUCT DATA SHEET

Product Description

Bluenenergy Azure Rhodium API CJ-4/SN series is high performance diesel engine oil formulated with highly refined fully synthetic base stocks and advanced technology additives to provide reliable performance in the latest emission designs, including those with EGR systems, as well as satisfying the needs of older engines. It may be used in naturally aspirated and turbocharged diesel and petrol engines, providing excellent protection even under the most strenuous conditions.

Features & Benefits

- Outstanding oxidation & thermal stability reduces sludge deposits and keeps the engine cleaner.
- Excellent engine protection by providing outstanding protection against wear.
- Improved fuel economy.
- Excellent dispersancy provides outstanding soot control in Exhaust Gas Recirculation (EGR) systems.
- Extended TBN reserves provide improved acid neutralization and corrosion protection, which helps in extending oil drain intervals.

Specifications

Bluenenergy Azure Rhodium CJ-4/SN series meets or exceeds following International and Builder specification:

- API CJ-4, CI-4 Plus, CI-4, CH-4, CF, CF-2, SN, SM, SL, SJ
- ACEA E9/E7
- MTU OIL Category 2.1
- MACK EO-O Premium Plus
- Detroit Diesel Power Guard 93K218
- CUMMINS CES 20081/76/77
- CAT ECF-3
- MB 228.31
- VOLVO VDS-4
- MAN 3575
- Deutz DQC-III-10 LA
- Renault VI RLD-3

Applications

- Automotive diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Naturally aspirated or turbo-charged engines.
- Fuel injected or indirect injection diesel engines fitted with blow-by recirculation systems

Typical Characteristics

Bluenenergy Azure Rhodium	Test Method	Units	10W30	10W40
Density @ 15 °C	ASTM D 4052	gm/cc	0.868	0.875
Viscosity @ 100 °C	ASTM D 445	cSt	10.4	14.4
Viscosity @ 40 °C	ASTM D 445	cSt	62.6	96
Viscosity Index	ASTM D 2270	-	155	155
Pour Point	ASTM D 97	°C	-39	-39
Flash Point (COC)	ASTM D 92	°C	215	236
Total Base Number	ASTM D 2896	mg KOH/g	10.4	10.4
Sulphated Ash	ASTM D 874	% wt	1.0	1.0
CCS Viscosity	ASTM D 5293	cP @-25	6050	6200

These characteristics are typical of current product methods whilst future production will confirm to Bluenenergy lubricants specifications, variations in these physical characteristics may occur.

For further information, please contact: info@Bluenenergylubes.com