



Hydra HVI Hydraulic Oil Series

A high-performance Hydraulic Oil

PRODUCT DATA SHEET

Product Description

A high-viscosity index, zinc-free anti wear hydraulic fluid formulated with high quality HVI base oils & advanced ashless additive technology to provide reliable protection & efficient performance in hydraulic & fluid power systems. It offers excellent wear protection, hydrolytic stability, & dependable operation across a wide temperature range, making it suitable for demanding applications, including systems exposed to high moisture conditions.

Features & Benefits

- Very high viscosity index and excellent shear stability, ensures long pump life under extreme conditions.
- Outstanding thermal & oxidation stability helps in extending life of oil and filter.
- Outstanding demulsibility aids in rapid water separation and provides excellent hydrolytic stability.
- Excellent anti-wear property of oil provides maximum equipment life, under severe duty & high loads.
- Excellent protection from rust and corrosion of multi-metallurgy system components.
- Good anti-foam and air release characteristics, designed by using silicon free additive components.

Specifications

Hydra HVI series meets or exceeds following International and Builder specifications:

- DIN 51524 Part 3 HVLP type
- ISO 6743/4 HV
- Denison HF-0, HF-2 (T6H20C)
- VICKERS M-2950S, -I-286
- Cincinnati Machine P68, P69, P70
- VICKERS 35VQ25, 104C

Applications

These HVI oils are designed for use in Hydraulic applications subjected to wide temperature variations.

- Suitable for use in hydraulics of Marine, Industrial & Earth moving; where temperatures vary seasonally.
- Applications where HVI anti-wear lubricant is required: servicing gears & bearings, air compressors etc.

Typical Characteristics

Hydra HVI Oil	Test Method	Units	15	22	32	46	68	100	150
ISO Viscosity Grade	ISO 3448	-	15	22	32	46	68	100	150
Density @ 15 °C	ASTM D 4052	gm/cc	0.845	0.864	0.870	0.878	0.880	0.887	0.894
Viscosity @ 40 °C	ASTM D 445	cSt	15.6	22.9	32.4	46.8	68.9	100.8	150.2
Viscosity @ 100 °C	ASTM D 445	cSt	3.99	5.12	6.46	8.41	11.27	13.21	16.85
Viscosity Index	ASTM D 2270	-	161	160	156	156	156	128	120
Pour Point	ASTM D 97	°C	-39	-39	-36	-36	-36	-33	-33
Flash Point (COC)	ASTM D 92	°C	174	204	224	230	234	246	252
Copper Strip Corrosion	ASTM D 130	-	1A	1A	1A	1A	1A	1A	1A
Rust Characteristics Proc B	ASTM D 665	-	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Foam Seq I,II,III	ASTM D 892	ml/ml	20/0	20/0	20/0	20/0	20/0	20/0	20/0
Demulsibility, 40/40/0	ASTM D 1401	min	10	10	15	20	20	25	30
TAN, mg KOH/g	ASTM D 2896	-	0.6	0.6	0.6	0.6	0.6	0.6	0.6

The above figures are typical of blends with normal production tolerance and do not constitute a specification.