

BLUENERGY YALE VELOCITY API SP SERIES

High Performance Multigrade Gasoline Engine Oil

PRODUCT DATA SHEET

Product Description

Bluenergy yale velocity 20W50 - SP is designed with high quality base stocks and advanced technology additive system to provide high level of protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most motorcycle manufacturers and is suitable for use in 4 stroke gasoline engines, naturally aspirated or turbo charged engines, operating in all round seasons and adapted to vehicles equipped with catalytic converters running on unleaded fuels.

Features & Benefits

- Excellent oxidation & thermal stability, helps in extending oil drain intervals.
- Very good shear stability and excellent viscosity temperature behaviour.
- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy, reduces sludge formation which improves engine cleanliness.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.
- Easier cold starts and improved fuel economy compared to mono-grade engine oils.

Specifications

Bluenergy yale Velocity 20W50 - SP meets or exceeds following International and Builder specification:

- API SP, SN, SM, SL, CF

Applications

Bluenergy yale Velocity 20W50 - SP is suitable for use in following:

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged engines.
- Fuel injected or indirect injection diesel engines fitted with blow-by recirculation systems.

TYPICAL CHARACTERISTICS

Bluenergy yale Velocity	Test Method	Units	20W-50
Density @ 15 °C	ASTM D 4052	gm/cc	0.890
Viscosity @ 100 °C	ASTM D 445	cSt	20.4
Viscosity @ 40 °C	ASTM D 445	cSt	175
Viscosity Index	ASTM D 2270	-	136
Pour Point	ASTM D 97	°C	-24
Flash Point (COC)	ASTM D 92	°C	236
Total Base Number	ASTM D 2896	mg KOH/g	7.0
CCS Viscosity	ASTM D 5293	cP @-15	6060

These characteristics are typical of current product methods whilst future production will confirm to Bluenergy lubricants specifications, variations in these physical characteristics may occur.

Protect the Environment

Take used oil to an authorized collection point or to be recycled. Do not discharge used or new oil into drains, soil or water.

Additional Information

Based on available information, this product is not expected to produce adverse effect on health when used for the

Applications referred to above and the recommendations provided in safety data sheet are followed. guidance on health and safety is available on the appropriate material safety data sheet(MSDS) which can be obtained from www.Bluenergylubricants.com